







MRL-03LC





Excellent equipment for automated kitchen

Auto lift

Light up 5 seconds before finishing and sound buzzer when completed



Supply hot water to utilize exhaust heat Enabling to continue cooking





1

Digital Timer 1 sec. ~ 99 min. 99 sec. by 1 sec. English Touch Panel (MRL-03C and MRL-06C)




Install a pool to store hot water heated by exhaust heat - High grade model only

Wave bottom to make strong boiling High grade model only



Exhaust hot air and keep comfortable kitchen

Heat Effeciency 60%



Stainless Steel SUS304 - tank SUS430 - body 111

Hole Heat Pipe

Registered utility model

Model	External Dimension (mm)				Table	Durlet	Tank	Electricity	Gas Consumption				Gas Connection		Weight
	Width	Depth	Height	Back	Tank	Basket	Amout (Liter)	100V/1 <i>φ</i> (50/60Hz)	Te	own Gas	LP Gas		Town Gas	LPGas	(kgs)
MRL-03L(R)C	330	700	800	150	1	3	25	43W	9.3kw	8,000kcal/h	9.3kw	0.67kg/h	15A	15A	62
MRL-04C	600	600	800	150	1	4	36	33W x 2	13.4kw	11,500kcal/h	13.4kw	0.96kg/h	15A	15A	77
MRL-06C	600	700	800	150	1	6	48	43W x 2	18.0kw	15,500kcal/h	18.0kw	1.29kg/h	15A	15A	102

High grade model

Model	External Dimension (mm)				Tank	Basket		Electricity $100V/1\phi$	Gas Consumption				Gas Cor	nnection	Weight
	Width	Depth	Height	Back	Tarik	Dasket		(50/60Hz)	T	own Gas	LP Gas		Town Gas	LP Gas	(kgs)
MRH-057LB	640	780	800	410	1	6	33	43W	20.9kw	18,000kcal/h	20.9kw	1.5kg/h	15A	15A	121

* 1) Voltage conversion on request. 2) Electric models available

ビ Maruzen

General Commercial Kitchen Appliances & Equipment 19-18, 2-Chome Negishi, Taito-Ku, Tokyo, Japan Tel 81-3-5603-7722 Fax 81-3-5603-7728 http://www.maruzen-kitchen. co.jp