

Maruzen Steam Convection Oven (Super Steam)

SSC-10DCNSTU



SSC-20DCNU



*Equipment with Navigation Display, hot air, Combination, steam, re-calefaction, each cooking mode.
The cooking mode is rigerstered 9 steps, 99 menus in max. This is already input 1 to 50 data.
You can add a new data in kana, alphabet and number.*

Super Steam (Deluxe Series)

Model	External Dimension (mm)			Electricity (3 φ 200v) (50/60Hz)	Feed Water Inlet		Drain Outlet	capacity for hotel bread
	Width	Depth	Height		Soft Water	Raw Water		
SSC-06DCNSTU	1,030	750	1,440	9.3	15A	15A	φ 48	1/1 size*6pcs
SSC-06DCNU	1,030	750	840	9.3	15A	15A	φ 48	1/1 size*6pcs
SSC-10DCNSTU	1,030	750	1,700	15.4	15A	15A	φ 48	1/1 size*10pcs
SSC-10DCNU	1,100	750	1,100	15.4	15A	15A	φ 48	1/1 size*10pcs
SSC-20DCNU	1,190	780	1,885	34	15A	15A	32A	1/1size*20pcs
SSC-24DCNU	1,190	1,100	1,365	33.8	15A	15A	32A	1/1 size*24pcs (2/1 size*12pcs)
SSC-40DCNU	1,190	1,100	1,885	55.4	15A	15A	32A	1/1 size*40pcs (2/1 size*20pcs)

※ NSTU is equipped with the softening apparatus and counter, and NU is equipped with the softening apparatus.

Super Steam (Standard Series)

Model	External Dimension (mm)			Electricity (3 φ 200v) (50/60Hz)	Feed Water Inlet		Drain Outlet	capacity for hotel bread
	Width	Depth	Height		Soft water	Raw Water		
SSC-06SCNSTU	1,030	750	1,440	9.3	15A	15A	φ 48	1/1size*6 pcs
SSC-06SCNU	1,030	750	840	9.3	15A	15A	φ 48	1/1 size*6 pcs
SSC-10SCNSTU	1,030	750	1,700	15.4	15A	15A	φ 48	1/1 size*10 pcs
SSC-10SCNU	1,030	750	1,100	15.4	15A	15A	φ 48	1/1 size*10 pcs
SSC-20SCNU	1,190	780	1,885	34	15A	15A	32A	1/1 size*20 pcs
SSC-24SCNU	1,190	1,100	1,365	33.8	15A	15A	32A	1/1 size*24 pcs (2/1 size*12 pcs)
SSC-40SCNU	1,190	1,100	1,885	55.4	15A	15A	32A	1/1 size*40 pcs (2/1 size*20 pcs)

※ NSTU is equipped with the softening apparatus and counter, and NU is equipped with the softening apparatus.

■ Softening apparatus of NSTU and NU



Cartridge Type (RPS-10LN)
SSC-06.10



Full Automatic Type (MS-10)
SSC-20.24.40