

Maruzen Hot and Cool Cart

■ Reversible, Self – propelled Type

Model	Row	External Dimension (mm)			Tray	Layer	Pitch (mm)	Electricity (50/60Hz)	Electric Consumption	Caster	Speed (km/h)	Weight (kgs.)
		Width	Depth	Height								
MTC-24RJB	4	1,400	780	1,345	24	6	125	3 ϕ /200V	2.32/2.38	4	Forward 3.0 Forward 1.5 Back 1.0	274
MTC-28RJB		1,400	780	1,470	28	7	125		2.38/2.44	4		287
MTC-32RJB		1,400	780	1,595	32	8	125		2.73/2.79	4		300
MTC-36RJB		1,400	780	1,720	36	9	125		2.73/2.79	4		313
MTC-40RJB		1,400	780	1,845	40	10	125		2.73/2.79	4		326
MTC-42RJHB	6	2,050	780	1,470	42	7	125		3.46/3.58	6		393
MTC-48RJHB		2,050	780	1,595	48	8	125		3.99/4.11	6		414
MTC-54RJHB		2,050	780	1,720	54	9	125		3.99/4.11	6		435
MTC-42RJKB		2,050	780	1,470	42	7	125		3.46/3.58	6		393
MTC-48RJKB		2,050	780	1,595	48	8	125		3.99/4.11	6		414
MTC-54RJKB		2,050	780	1,720	54	9	125	3.99/4.11	6	435		

■ General, Self – propelled Type

Model	Row	External Dimension (mm)			Tray	Layer	Pitch (mm)	Electricity (50/60Hz)	Electric Comsumption	Caster	Speed (km/h)	Weight (kgs.)	
		Width	Depth	Height									
MTC-24SJB	4	1,300	780	1,345	24	6	3 ϕ /200V	2.32/2.38	4	Forward 3.0 Forward 1.5 Back 1.0	254		
MTC-28SJB		1,300	780	1,470	28	7		2.38/2.44	4		264		
MTC-32SJB		1,300	780	1,595	32	8		2.73/2.79	4		274		
MTC-36SJB		1,300	780	1,720	36	9		2.73/2.79	4		284		
MTC-40SJB		1,300	780	1,845	40	10		2.73/2.79	4		294		
MTC-42SJHB	6	1,900	780	1,470	42	7		3 ϕ /200V	3.46/3.58		6	Forward 3.0 Forward 1.5 Back 1.0	358
MTC-48SJHB		1,900	780	1,595	48	8			3.99/4.11		6		374
MTC-54SJHB		1,900	780	1,720	54	9			3.99/4.11		6		390
MTC-42SJKB		1,900	780	1,470	42	7			3.46/3.58		6		358
MTC-48SJKB		1,900	780	1,595	48	8			3.99/4.11		6		374
MTC-54SJKB		1,900	780	1,720	54	9	3.99/4.11		6	390			

■ Reversible, Self – Manual Type

Model	Row	External Dimension (mm)			Tray	Layer	Pitch (mm)	Electricity (50/60Hz)	Electric Consumption	Caster	Weight (kgs.)
		Width	Depth	Height							
MTC-24RB	4	1,400	780	1,345	24	6	125	3 ϕ /200V	2.12/2.18	4	217
MTC-28RB		1,400	780	1,470	28	7	125		2.18/2.24	4	230
MTC-32RB		1,400	780	1,595	32	8	125		2.573/2.579	4	243
MTC-36RB		1,400	780	1,720	36	9	125		2.53/2.59	4	256
MTC-40RB		1,400	780	1,845	40	10	125		2.53/2.59	4	269
MTC-42RB	6	2,050	780	1,470	42	7	125		3.26/3.38	6	336
MTC-48RB		2,050	780	1,595	48	8	125		3.79/3.91	6	357
MTC-54RB		2,050	780	1,720	54	9	125		3.79/3.91	6	378

■ General, Self – Manual Type

Model	Row	External Dimension (mm)			Tray	Layer	Pitch (mm)	Electricity (50/60Hz)	Electric Consumption	Caster	Weight (kgs.)
		Width	Depth	Height							
MTC-24SB	4	1,300	780	1,345	24	6	125	3 ϕ /200V	2.32/2.38	4	197
MTC-28SB		1,300	780	1,470	28	7	125		2.38/2.44	4	207
MTC-32SB		1,300	780	1,595	32	8	125		2.73/2.79	4	217
MTC-36SB		1,300	780	1,720	36	9	125		2.73/2.79	4	227
MTC-40SB		1,300	780	1,845	40	10	125		2.73/2.79	4	237
MTC-42SB	6	1,900	780	1,470	42	7	125		3.46/3.58	6	301
MTC-48SB		1,900	780	1,595	48	8	125		3.99/4.11	6	317
MTC-54SB		1,900	780	1,720	54	9	125		3.99/4.11	6	333